



PLUSCO 001

Coating & Varnish Remover

DESCRIPTION

Plusco 001 is a USDA authorized gel base coating and varnish remover. Penetrates deep to remove paint, epoxy paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials from all surfaces. Washes off with water or solvent. Safe to use on metal, brick, ceramic, wood and tile surfaces. Clings to all vertical surfaces.

APPLICATIONS

Works hard to remove paint, epoxy, lacquer, carbon deposits and silicone. Areas of use include auto dealers, paint shops, factories, schools, farms, oil rigs, bottling plants, lumber mills and cement plants.

FEATURES & BENEFITS

- Gel based formula clings to vertical surfaces, allowing longer contact time
- Removes a wide range of paints and surface sealers from metal, concrete and wood
- Ease of use—simply spray on and wipe or rinse

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: Excellent
TOXICITY: 25 ppm OSHA TLV
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year+
COLD STABILITY: 0°F
PHOSPHATES: N/A

FLASH POINT: None
FLAME EXTENSION: None
SOLUBILITY IN WATER: 15%
SPECIFIC GRAVITY: 1.20
% VOLATILE BY VOLUME: 97% +
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Medium
BIODEGRADABILITY: No

LABEL INFORMATION

Plusco 001

Coating & Varnish Remover

Gel formulation paint remover quickly removes paint, epoxy paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run. This formula has been authorized by the USDA for use in federally inspected meat and poultry plants.

For use by auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices. For use on metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry and cylinders.

DIRECTIONS: Shake well before using. Holding can eight to ten inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow product to complete blistering before removing.


CAUTION: Contains methylene chloride, which has been shown to cause cancer in certain laboratory animals. Risk to health depends on level and duration of exposure.

CAUTION: Contents under pressure. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting. Vapor harmful. Use this product outdoors if possible. If you must use it indoors, open all windows and doors or use other means to ensure fresh air movement during use. Avoid prolonged breathing of vapor or contact with skin or eyes. In case of contact with eyes, flush thoroughly with water. **INHALATION:** Remove to fresh air. If not breathing administer CPR and seek immediate medical attention. **INGESTION:** Give large quantities of water. Do not induce vomiting without consulting doctor or poison control. Seek medical attention immediately. **EYES:** Flush eyes with water for 15 min. Seek medical attention. **SKIN:** Wash with soap and water. Call a physician immediately.

WARNING: This product contains chemical(s) known to the State of California to cause cancer.

CONTAINS (CAS#): Methylene Chloride (75-09-2), Propane/n-Butane (68476-86-8), Methanol (67-56-1), Methylcellulose (9004-65-3), Petroleum Wax(64742-43-4).

HEALTH	3
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 16 oz cans per case, 13 oz net weight