



PLUSCO

Product Data Sheet

PLUSCO 195 **Premium Pipe Storage Compound**

PLUSCO 195 Premium Pipe Storage Compound is designed to control the formation of rust and pitting on threads of oilfield tubular goods during storage. It is formulated using the most up to date high tech rust and corrosion inhibitors available today. This high tech package of inhibitors is found to be very effective under high humidity and moisture conditions thus reducing the risk of rust and pitting during extended storage. These high tech inhibitors provide a neutralization effect on the metal pipe surface, thus providing a new dimension in corrosion control.

PLUSCO 195 Premium Pipe Storage Compound also contains anti-oxidants, which stabilize the corrosion inhibitors to further retard rust formation making it effective over an extended period of time. The golden translucent color of **195 Premium Pipe Storage Compound** leaves pipe doped with **PLUSCO 195** easily identifiable and has a self-healing affect.

Typical Specifications

Color	Golden Translucent
Consistency	Smooth
Texture	Buttery
Base Thickener	Calcium
Classification	Corrosion Inhibitors
Penetration, ASTM D-217 @ 77°F	340
NLGI Grade	1
Specific Gravity @ 77°F	0.895
Density lbs/gal @ 77°F	7.5
Flash Point, ASTM D-92	>350°F
Type Inhibitor	Anionic
Water Solubility	Insoluble
Salt Spray Test, ASTM B-117	Passed 2000+ hours
Shelf Life (unopened container)	2 Years
Other Properties	Rust Inhibited Corrosion Inhibited Oxidation Inhibited Non-Toxic

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.