



PLUSCO

Product Data Sheet

PLUSCO 320 **Premium Black OD Kote**

PLUSCO 320 is a fast drying, black OD pipe coating suitable for use on oilfield tubing, casing, drill pipe, wash pipe, or other tubular goods. It may be sprayed using conventional equipment, or applied by brush, roller, or dipping. It will dry to a glossy black finish, and may be stenciled using conventional means. It should not be used in the ID of pipe that is to be drifted because the film, which will be left will slightly affect the ID.

TYPICAL SPECIFICATIONS

Color	Black
Viscosity, #4 Ford Cup	19 - 23 Sec.
Percent Solids	50%
VOC	3.5 LBS / Gallon
Density	7.0 LBS / Gallon

PLUSCO 320 should be applied to metal surfaces which are brushed to remove any seal or surface rust. Conventional pipe cleaning machines provide satisfactory results for surface preparation.

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.