



PLUSCO

Product Data Sheet

PLUSCO 504 **Valve Stick Lubricant & Sealant**

PLUSCO 504 Heavy Duty Valve Stick Lubricant and Sealant is formulated for use in hydrocarbon services in a convenient stick form. **PLUSCO 504** is recommended for use in gasoline, diesel kerosene, gas-well condensate and various types of jet and aviation fuels. It is also recommended for use in solvents like mineral spirits, xylene or various LPG compositions.

PLUSCO 504 is a blend of synthetic oils that resists washout by water and petroleum hydrocarbons. It is a superior valve lubricant and sealant, which minimizes friction during valve operation. **PLUSCO 504** contains rust and corrosion inhibitors, which prevents valve freeze-ups and assures continuous sealing during adverse operation conditions. **PLUSCO 504** Valve Stick Lubricant and Sealant will allow continuous valve operation between lubricating intervals.

PLUSCO 504 Valve Stick Packing is formulated for applications to valves equipped with bottom head fittings. **PLUSCO 504** is available in convenient "J" stick form.

TYPICAL SPECIFICATIONS

COLOR	TAN
CLASSIFICATION	SYNTHETIC BASE
CONSISTANCY	TACKY
THICKNER	ORGANIC COMPOSITION
FLASH POINT (ASTM D-92)	NOT APPLICABLE
PERCENT SOLIDS	48.0 %
CLAY FILLERS	NONE
SPECIFIC GRAVITY@77°F	1.586
DENSITY	13.2 lbs./gal
SERVICE TEMPERATURE RANGE	40°F TO 400°F
OTHER PROPERTIES	GOOD TENACITY RUST RESISTANT RESIST WASHOUT

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.