

PLUSCO

Product Data Sheet

PLUSCO 601

Plus Lube Film Forming Lubricant Made with PLUSLON®


PLUSCO 601 Plus Lube is a highly concentrated film forming lubricant formulated to decrease lubrication internals and increase equipment productivity. **PLUSCO 601 Plus Lube** is made with PLUSLON® which is inert to acids, caustics additives, various hydrocarbons including gasoline and solvent.

PLUSCO 601 Plus Lube film forming properties exhibits an extremely low coefficient of friction through its film forming action thus separating surface-to-surface contact and thereby conserving energy. The residual film of PLUSLON® provides instant lubrication to the critical areas of the equipment which require instant lubrication during start up. This film forming lubricant reduces equipment wear and guards against the effects of corrosion and damage from rust to vital equipment areas.

PLUSCO 601 Plus Lube is an extremely versatile lubricant with a broad range of applications. **PLUSCO 601 Plus Lube** is effective for certain bearing applications operating on low torque and under extreme pressure conditions. **PLUSCO 601 Plus Lube** can be used as an additive to gear reduction units, manual transmissions, chain drive units, conveyor systems, to bolts and studs and can be used as a gasket dressing.

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.



PLUSCO

Product Data Sheet

PLUSCO 601

Plus Lube Film Forming Lubricant Made with PLUSLON®

TYPICAL SPECIFICATIONS

Type Lubricant	Film Forming Concentrate
Color	Green
Base Thickener Classification	Inorganic
Active Component	PLUSLON®
Appearance	Smooth
Consistency	Buttery
Specific Gravity @ 77° (Avg.)	1.08
Density Lbs. / gal.	9.0
Flash Point ASTM D-29 (COC)	+ 400°F
Dropping Point ASTM D-566	Non Melt
Oil Viscosity ASTM D-2161 100°F SUS	750
Penetration Worked @ 77°F ASTM D-217	295 - 310
NLGI Grade (Avg.)	1.5
Rust Prevention ASTM D-1743	Pass
Other Features	EP/Anti-wear Rust Corrosion Inhibited, Oxidation Inhibited Water Resistant

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.