



# PLUSCO

## Product Data Sheet

### **PLUSCO 855-MG INHIBITED SUCKER ROD MAKE-UP & BREAK-OUT LUBE**

#### **Typical Specifications**

Type Lubricant	Aluminum Complex
Thickener	Aluminum Benzoate / Stearate
Color	Grayish Black
Active Component	Molybdenum-Disulfide & Graphite
Cone Pen ASTM D-217 (Worked)	345 – 385, 295 – 335 265 - 295
NLGI Grade	No. 0 1 2
Bearing Leakage D-1263	Pass
Dropping Point ASTM-D-566	525°F±
Characteristics of Oil	
Viscosity @ 100°F	1450 SUS
Viscosity @ 200°F	98 SUS
Viscosity Index	78
Texture	Buttery
Water Resistance	Excellent
H <sub>2</sub> S Resistance	Excellent
Other Characteristics	Fully Inhibited - EP. Anti-Wear, Anti-Oxidant, Anti-H <sub>2</sub> S Anti-Rust and Corrosion Inhibited

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.