



PLUSCO

Product Data Sheet

PLUSCO 863 **Jack-Up Leg Grease**

PLUSCO 863 is a high quality leg grease which is designed for use on drilling rigs, spud barges or lift boats. Its EP properties provide good protection, and its highly adhesive nature enables it to stay in place when applied. **PLUSCO 863** is made with Molybdenum Disulfide and graphite, which together are known for superior lubricating properties and film forming characteristics in wet environments. **PLUSCO 863** resists washout and will not sheen out on water.

In addition to its application to jack-up legs, **PLUSCO 863** can also be used as an open gear lube on marine equipment, on wire rope or cable, or in other applications where resistance to washout is desirable.

TYPICAL SPECIFICATIONS

Color	Dark Gray / Black
Appearance	Smooth Buttery
Worked Penetration, (ASTM-D-217)	265 - 295
NLGI Number	#2
Density, (lbs. / gal.)	9.1
Drop Point, (ASTM-D-2265)	200°F
Flash Point	375°F
Water Resistant	Excellent
Active Component	Molybdenum Disulfide
Classification	High Density

Packaging: 35 Lb. Plastic Pails, 125 Lb. Drums, 450 Lb. Drums

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.