#PLUSCO

SAFETY DATA SHEET

1. Identification

Product identifier 181ET, ET Nickel Base Anti-Seize

Other means of identification

SDS number 181ET.001
Product code PLU181ET

Recommended use Anti-seize compound.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company namePLUSCO, Inc.Address14518 Henry Road

Houston, TX 77060

Telephone 713-880-0316
Website www.plus-co.com
Emergency phone number 1-800-275-1875

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1

Carcinogenicity Category 2
Specific target organ toxicity, repeated Category 1

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. Suspected of causing cancer. Causes damage to organs

through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must

not be allowed out of the workplace. Wear protective gloves/protective clothing/eye

protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If

skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before

reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Combustible.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

181ET, ET Nickel Base Anti-Seize SDS US

Chemical name	CAS number	%
Mineral Oil	NA	50 - < 60
Nickel	7440-02-0	10 - < 20
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	5 - < 10
Magnesium oxide	1309-48-4	5 - < 10
Aluminum	7429-90-5	3 - < 5

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eve contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs. Get medical attention if

symptoms occur.

effects.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed **General information** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Dry sand. Dry chemicals. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire. Carbon dioxide (CO2).

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Specific methods General fire hazards Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible. No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up The product is immiscible with water and will sediment in water systems. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

181ET, ET Nickel Base Anti-Seize SDS US Store locked up. Keep away from heat and sources of ignition. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Aluminum (CAS 7429-90-5)	PEL	5 mg/m3	Respirable dust.
		15 mg/m3	Total dust.
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m3	Mist.
Magnesium oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.
Mineral Oil (CAS NA)	PEL	5 mg/m3	Mist.
Nickel (CAS 7440-02-0)	PEL	1 mg/m3	
US. ACGIH Threshold Limit	Values	Ü	
Components	Туре	Value	Form
Aluminum (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Magnesium oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
Mineral Oil (CAS NA)	TWA	5 mg/m3	Inhalable fraction.
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m3	Respirable.
		5 mg/m3	Welding fume or pyrophoric powder.
		10 mg/m3	Total
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
paramine (er le e :	TWA	5 mg/m3	Mist.
Mineral Oil (CAS NA)	STEL	10 mg/m3	Mist.
,	TWA	5 mg/m3	Mist.
Nickel (CAS 7440-02-0)	TWA	0.015 mg/m3	
logical limit values	No biological exposure limits noted for	or the ingredient(s).	
oropriate engineering ntrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
ividual protection measures, Eye/face protection	such as personal protective equipmedical goggles are recommended		
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.		
Skin protection Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
neral hygiene nsiderations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.		

181ET, ET Nickel Base Anti-Seize SDS US

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Semi-solid. Viscous.

Color Gray.

Odor Petroleum.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point 450.0 °F (232.2 °C) Cleveland Open Cup

Not available.

Not available.

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressureNot available.Vapor densityNot available.Relative density1.37 g/cm3

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong acids. Strong oxidizing agents. Phosphorus. Chlorine.

Hazardous decomposition

products

Carbon oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

181ET, ET Nickel Base Anti-Seize SDS US

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-54-7) Nickel (CAS 7440-02-0)

2B Possibly carcinogenic to humans.

Known To Be Human Carcinogen.

NTP Report on Carcinogens

Distillates (petroleum), hydrotreated heavy paraffinic

(CAS 64742-54-7)

Nickel (CAS 7440-02-0) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** Nickel (CAS 7440-02-0) Aquatic Crustacea EC50 Water flea (Daphnia magna) 1 mg/l, 48 hours 1 mg/l, 48 Hours LC50 7.35 - 12.12 mg/l, 96 hours Calanoid copepod (Eurytemora affinis)

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

181ET, ET Nickel Base Anti-Seize SDS US

^{*} Estimates for product may be based on additional component data not shown.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Nickel (CAS 7440-02-0)

LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Nickel	7440-02-0	10 - < 20	
Aluminum	7429-90-5	3 - < 5	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Nickel (CAS 7440-02-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Aluminum (CAS 7429-90-5)

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

Magnesium oxide (CAS 1309-48-4)

Mineral Oil (CAS NA)

Nickel (CAS 7440-02-0)

181ET, ET Nickel Base Anti-Seize

Version #: 01 Revision date: - Issue date: 1-January-2019

US. New Jersey Worker and Community Right-to-Know Act

Aluminum (CAS 7429-90-5) Magnesium oxide (CAS 1309-48-4)

Mineral Oil (CAS NA) Nickel (CAS 7440-02-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum (CAS 7429-90-5)

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

Inventory name

Magnesium oxide (CAS 1309-48-4)

Mineral Oil (CAS NA) Nickel (CAS 7440-02-0)

US. Rhode Island RTK

Aluminum (CAS 7429-90-5) Nickel (CAS 7440-02-0)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Nickel (CAS 7440-02-0)

International Inventories

Country(s) or region

Country(s) or region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 1-January-2019

Revision date - Version # 01

United States & Puerto Rico

HMIS® ratings Health: 2*

Flammability: 1 Physical hazard: 0

NFPA ratings



Disclaimer

PLUSCO, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

181ET, ET Nickel Base Anti-Seize SDS US

Yes

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).