

# SAFETY DATA SHEET

### 1. Identification

Product identifier 438 Inhibited Cable Lube

Other means of identification

SDS number 438.001 Product code PLU438

Recommended use Industrial lubricant.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

**Company name** PLUSCO, Inc. **Address** 14518 Henry Road

Houston, TX 77060

Telephone713-880-0316Websitewww.plus-co.comEmergency phone number1-800-275-1875

## 2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation.

**Precautionary statement** 

Prevention Wash thoroughly after handling. Wear eye protection/face protection. Wear protective gloves.

Response If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off

contaminated clothing and wash before reuse.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	80-90
Asphalt	8052-42-4	10-20
Stoddard solvent	8052-41-3	1-5

438 Inhibited Cable Lube SDS US

932251 Version #: 01 Revision date: - Issue date: 11-February-2016

## 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

vision. Skin irritation. May cause redness and pain.

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

**General information** 

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

**Specific methods**Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

# **Environmental precautions**

7. Handling and storage Precautions for safe handling

Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

ordaning any moompatismacs of the established

# 8. Exposure controls/personal protection

### Occupational exposure limits

## US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.	
·		2000 mg/m3		
		500 ppm		
Stoddard solvent (CAS 8052-41-3)	PEL	2900 mg/m3		
,		500 ppm		

### **US. ACGIH Threshold Limit Values**

Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	

### **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Туре	Value	Form	
Asphalt (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3		
,	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
Stoddard solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3		
•	TWA	350 mg/m3		

Biological limit values

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Skin protection

Other Wear appropriate chemical resistant clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.

Form Viscous liquid.

Color Black.

Odor Petroleum.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point > 350.0 °F (> 176.7 °C) Cleveland Open Cup

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density 0.88 g/cm3 (77 °F (25 °C))

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid**Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** 

products

Carbon oxides.

### 11. Toxicological information

# Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain.

### Information on toxicological effects

# **Acute toxicity**

Components Species Test Results

Asphalt (CAS 8052-42-4)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg, 24 hours

Inhalation

LC50 Rat > 94.4 mg/m3

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Asphalt (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

Distillates (petroleum), hydrotreated heavy naphthenic

(CAS 64742-52-5)

Stoddard solvent (CAS 8052-41-3) 3 Not classifiable as to carcinogenicity to humans.

**NTP Report on Carcinogens** 

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

3 Not classifiable as to carcinogenicity to humans.

Persistence and degradability No data is available on the degradability of this product.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

Stoddard solvent (CAS 8052-41-3) 3.16 - 7.15

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations**Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

438 Inhibited Cable Lube SDS US

932251 Version #: 01 Revision date: - Issue date: 11-February-2016

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

## Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

## 15. Regulatory information

**US** federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Asphalt (CAS 8052-42-4)

LISTED

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

### **US** state regulations

## **US. Massachusetts RTK - Substance List**

Asphalt (CAS 8052-42-4)

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Stoddard solvent (CAS 8052-41-3)

## **US. New Jersey Worker and Community Right-to-Know Act**

Asphalt (CAS 8052-42-4)

Stoddard solvent (CAS 8052-41-3)

### US. Pennsylvania Worker and Community Right-to-Know Law

Asphalt (CAS 8052-42-4)

Stoddard solvent (CAS 8052-41-3)

## **US. Rhode Island RTK**

Not regulated.

## **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

## US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Asphalt (CAS 8052-42-4)

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates this product co	omplies with the inventory requirements administered by the governing country(s).	

# 16. Other information, including date of preparation or last revision

Issue date 11-February-2016

**Revision date** Version # 01

**HMIS®** ratings Health: 2

Flammability: 1 Physical hazard: 0

NFPA ratings



Disclaimer

PLUSCO, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).