



PLUSCO

Product Data Sheet

PLUSCO 752-68 WAYLUBE 68

PLUSCO WAYLUBE 68 is formulated from specially selected base oils fortified with rust preventative, lubricity agents, extreme pressure additives, demulsifiers and friction modifiers to lubricate and protect sliding parts on machine tools.

PLUSCO WAYLUBE 68 is blended from highly refined, hydrotreated paraffinic base oils with special additives to provide tackiness that allows the lubricants to adhere to slide ways during severe applications.

Benefits

- Provides a viscous hydrodynamic film for protection against wear and chatter
- Protects against rust and corrosion
- Prevents “slip-stick”, on machine ways

Application

- Ways on lathes, milling machines, boring machines and other machine tools where moving parts slide over each other
- Machine tool applications that require a dual purpose hydraulic way oil

Specifications

Specific Gravity	0.8664
Flash Point, ASTM D-92	380°F (193°C)
Pour Point, ASTM D-97	-26°F (-32°C)
Viscosity, Kinematic, cSt @ 40°C	69.20 Typ.
Viscosity, Kinematic, cSt @ 100°C	9.60 Typ.
Viscosity Index	119
Shelf Life (unopened container)	Two years

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.