



Product # 002

## Technical Data Report

# PLUSCO 002

## GEL TYPE COATING & VARNISH REMOVER

### DESCRIPTION

Plusco 002 is a USDA authorized gel base paint remover. Penetrates deep to remove paint, decals, gaskets, glue, graffiti, and labels from most surfaces. Washes off with water or solvent. Safe to use on metal, brick, ceramic, wood and tile surfaces. Clings to all vertical surfaces. Contains a chemical seal to prevent evaporation of paint removing solvents. Non-flammable.

### APPLICATIONS

For removal of coatings, paint, decals, epoxy, lacquer, varnish, gaskets, glue, carbon deposits, silicone, simulated wood paneling and other materials from metal, wood, brick, ceramic, and natural stone surfaces. Areas of use include auto dealerships, paint shops, factories, motels, hotels, schools, hospitals, homes and restaurants. NOTE: WILL DAMAGE PLASTICS.

### FEATURES & BENEFITS

- Versatile, multipurpose product removes a broad range of materials from most surfaces
- Thick formula clings to vertical surfaces, increasing contact time
- Works quickly and efficiently

### SPECIFICATIONS

**FORM:** Solvent-Based Liquid  
**ODOR:** Strong Chlorinated Solvent  
**COLOR:** Clear to Hazy  
**DETERGENCY:** Strong  
**TOXICITY:** 25 ppm OSHA PEL  
**WETTING ABILITY:** Excellent  
**STORAGE STABILITY:** 1 Year +  
**COLD STABILITY:** 0°F  
**PHOSPHATES:** None

**FLASH POINT:** None  
**BOILING POINT:** 104°F  
**SOLUBILITY IN WATER:** Emulsifies  
**SPECIFIC GRAVITY:** 1.20  
**% VOLATILE BY VOLUME:** 97.3% +  
**pH:** N/A  
**VISCOSITY:** Very Thick  
**EVAPORATION RATE:** Fast  
**BIODEGRADABILITY:** No

### LABEL INFORMATION

#### Plusco 002 COATING & VARNISH REMOVER

RUTHLESS is a USDA authorized gel base paint remover. Penetrates deep to remove paint, decals, gaskets, glue, graffiti, and labels from most surfaces. Washes off with water or solvent. Safe to use on metal, brick, ceramic, wood and tile surfaces. Clings to all vertical surfaces. Contains a chemical seal to prevent evaporation of paint removing solvents. Non-flammable.

**DIRECTIONS FOR USE: PAINT STRIPPING:** Preclean accumulations of dirt and grease with a heavy duty detergent. Allow to dry. Apply undiluted compound in a full heavy coat. Allow to stand until paint is thoroughly wrinkled or bubbled. Flush with water or solvent. Use a scraper or wire brush in cracks, crevices or on stubborn accumulation. On painted floors, a squeegee may be used to move the stripper from one area to another when finished, and compound may be reused. Add new product periodically. **GASKET REMOVAL:** Apply liberally to gasket and surrounding surfaces. Allow to stand for several minutes before removing gasket with scraper or wire brush. **DECAL REMOVAL:** Apply compound to decal. Allow to stand several minutes. Remove decal with scraper. Reapply if needed to remove adhesive residue. Rinse.

**CAUTION:** Contains Methylene chloride, which has been shown to cause cancer in certain laboratory animals. Risk to health depends on level and duration of exposure.


**DANGER! POISON.** Harmful or fatal if swallowed. Contains Methanol and Methylene chloride. Cannot be made nonpoisonous. Use only in well ventilated area. Store in cool area out of direct sunlight. Avoid prolonged breathing of vapor or contact with skin and eyes.

**FIRST AID: INTERNAL: Inhalation:** Remove to fresh air. If not breathing administer CPR and seek immediate medical attention. **Ingestion:** Give large quantities of water. Do not induce vomiting without consulting doctor or poison control. Seek medical attention immediately. **Eyes:** Flush eyes with water for 15 min. Seek medical attention. **Skin:** Wash with soap and water.

**WARNING:** This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

**CONTAINS (CAS#):** Methylene chloride (75-09-2), Methanol (67-56-1), Paraffin (8002-74-2), Nonionic Surfactant (127087-87-0).

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	B



### PACKAGING INFORMATION

Available in 4 x 1 gallons, 5 and 6 gallon pails and 55 gallon drums.