



Product # PLU008

Product Data Sheet

RUST RELEASE LUBRICANT

FOAMING PENETRATING & CUTTING OIL



DESCRIPTION

RUST RELEASE provides effective lubrication in a variety of metalworking applications. The anti-friction properties prolong tool life. For use on farm equipment, sports equipment, industrial equipment, marine and auto equipment. This fast penetrating product lubricates, displaces moisture, frees sticking parts, stops squeaks, stops rust and corrosion and provides long lasting protection.

APPLICATIONS

Formulated to loosen rusted parts and lubricate cutting or machining carbon alloys, stainless steel, chrome steel, copper, aluminum, magnesium, and bronze. Lubricates door hinges, chains, hoists, pulleys, cranes, fork lifts, sprockets, gears, blocks & tackle, conveyors, construction machinery, industrial parts and locks. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

FEATURES & BENEFITS

- Reduces metal-to-metal noise
- Resists rust and corrosion even in extreme conditions
- Prolongs tool life

SPECIFICATIONS

FORM: Oil Based Aerosol
ODOR: Mild Petroleum
COLOR: Brown
DETERGENCY: None
TOXICITY: 100 ppm OSHA TLV
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: 18" +
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 0.92
% VOLATILE BY VOLUME: 98%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: No

LABEL INFORMATION

RUST RELEASE
FOAMING PENETRATING & CUTTING OIL

This product is designed to be used on farm equipment, sports equipment, industrial equipment, marine and auto equipment. This fast penetrating product lubricates, displaces moisture, frees sticking parts, stops squeaks, stops rust and corrosion and provides long lasting protection.

DIRECTIONS: Remove protective cap. Point opening in desired direction. Hold container 6-12 inches from surface to be treated. Press button to spray. Spray liberally. Reapply periodically as required.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

CONTAINS (CAS #): Heavy Naphthenic Petroleum Distillate (64742-52-5), Propane/n-Butane (68476-86-8), Mineral Spirits (8052-41-3), Oxygenated Hydrocarbon (N/A).

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

12 – 20 oz cans per case, 16 oz net weight