



PLUSCO

Product Data Sheet

PLUSCO 400 **Inhibited Wireline Spray**

PLUSCO 400 is formulated using a balanced molecular weight polymer in a light mineral oil having a corrosion inhibitor package to provide total protection to the Wireline during adverse conditions. **PLUSCO 400** also contains special wetting agents, which allows the spray to penetrate the surface of the Wireline or cable down to the inner core of the Wireline. **PLUSCO 400 Wireline Spray** is designed to protect the complete Wireline from the effects of corrosive chemicals commonly found in downhole production. **PLUSCO 400** will protect the braided Wireline or cable against the corrosion effects of acids, caustics, salt water and most chemicals found in downhole operations.

PLUSCO 400 also provides a lubricating effect to the Wireline thus reducing most wear caused by continuous use. **PLUSCO 400 Wireline Spray** is designed, to be used in spray equipment commonly found mounted on most Wireline service units.

APPLICATIONS:

PLUSCO 400 Wireline Spray is recommended for braided Wireline, cables, and wire rope.

TYPICAL SPECIFICATIONS

Color	Light Amber
Consistency	Slightly Tacky
Odor	Mild Hydrocarbon
Viscosity #4 Ford Cup @ 77°F	14 - 18 Sec.
Pour Point, ASTM D-97	-28 °C
Flash Point ASTM D-92	138°F (59°C)
Shelf Life (unopened container)	2 Years

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.