



PLUSCO

Product Data Sheet

PLUSCO 440 **Synthetic Wireline Grease Seal**

PLUSCO 440 Synthetic Wireline Grease Seal is a synthetic based viscous, pumpable product specifically formulated for use in standard Wireline grease injection units and cable lubrications. **Plusco Wireline Grease Seal** is commonly referred to as “Honey Oil”. The product contains a specially balanced combination of corrosion inhibitors, H₂S/CO₂ inhibitors, anti-oxidants and anti-wear additives for reducing friction and keeping Wireline wear down to a minimum thus providing maximum protection to the line, even under the most severe operating conditions.

PLUSCO 440 Synthetic Wireline Grease Seal adheres to the line thereby reducing splatter or drip around the equipment being used or on the rig floor. **PLUSCO 440 Synthetic Wireline Grease Seal** prevents loss of well condensate and gases during wireline operations. Because the product has highly adhesive qualities, a protective film forms on the line further enhancing the performance of the anti-corrosion package. **PLUSCO 440 Synthetic Wireline Grease Seal** protects against acids, caustics, salt water and H₂S and other downhole chemicals.

All grades of **PLUSCO 440 Synthetic Wireline Grease Seal** are inhibited to provide protection against the corrosive effects of hydrogen sulfide / CO₂ up to 50,000 PPM or 5% concentration. For operations having higher concentrations of H₂S / CO₂ special orders can be prepared upon request.

PLUSCO 440 Synthetic Wireline Grease Seal is available in six grades with outstanding low and high temperature properties.

Specifications

Color	Golden Yellow
Texture	Tacky Liquid
Odor	Mild
Density, lbs/gal @ 77°F (25°C)	7.23
Specific Gravity, @ 77°F (25°C)	0.866
Flash Point, ASTM D-92	410°F (210°C)
Pour Point, ASTM D-97	-38°F (-39°C)
Viscosity, Kinematic, cSt @ 40°C	1500 - 2000
Rust Test ASTM D-665B @ 140°F (60°C)	Pass
Operating Temperatures	-17°F to +100°F (-27°C to +38°C)
Shelf Life (unopened container)	Two years

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.