



PLUSCO

Product Data Sheet

PLUSCO 506
“Peanut-Butter”
Gate Valve Lubricant and Sealant

PLUSCO 506 is a synthetic base lubricant and sealant designed for use in gate valves as well as in ball and plug valves. Its synthetic base resists washout by crude oil, distillates or other petroleum hydrocarbons. **PLUSCO 506** provides corrosion protection as well as extreme pressure lubrication to WKM type and other oilfield and pipeline valves.

PLUSCO 506 will service temperatures from - 20°F to +275°F, and can be applied by injection with a standard high-pressure grease gun. It is equivalent or superior to many products commonly referred to as “Peanut-Butter Lube,” including Lubchem 102 Special, Climax 110, and WKM 102. **PLUSCO 506** is available in 5 gallon pails, 16 and 55 gallon drums.

PLUSCO 506 can be used on:

WKM Gate Valves, McEvoy Valves, Rockwell Gate Valves, and Ingram Cactus Valves, as well as on a wellhead assemblies, bodies and pipeline valves.

TYPICAL SPECIFICATIONS

Color	Light Brown
Consistency	Extremely Tacky
Classification	Synthetic
Penetration ASTM D-217	280
NLGI Grade	2
Clay Fillers	None
Solubility (Water)	Insoluble
Other Properties	High Temp Rated Excellent Adhesion Resist Washout Non-Drying

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.