



PLUSCO

Product Data Sheet

PLUSCO 511 AG **Arctic Grade Valve Lubricant & Sealant**

PLUSCO 511 AG Valve Lubricant and Sealant is formulated as a low temperature valve lubricant and sealant for hydrocarbon service. **PLUSCO 511 AG** is a synthetic polymer composition, which is chemically stable, non-drying and is impermeable to water and gases. It is insoluble in water thus eliminating possible valve freeze-up. **PLUSCO 511 AG** is also resistant to hydrogen sulfide and provides good compressibility over a wide temperature range. **PLUSCO 511 AG** does not contain any bentonite clays or soaps, which can interfere with normal valve operation.

APPLICATION AREAS: Valve pumps, swivel joints and wellhead use.

TYPICAL SPECIFICATIONS

Color	Black
Base	Synthetic Polymer
Consistency	Heavy Viscous Liquid
Odor	Odorless
Flash Point	470°F
Specific Gravity @ 60°F	0.898
Service Temperature Range	-20°F to + 270°F
Dropping Point ASTM D	566°F

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.