



PLUSCO

Product Data Sheet

PLUSCO 740 **AW Hydraulic Oil**

Plusco 740 AW Hydraulic Oil is formulated to provide long fluid life while providing ultimate protection against equipment wear and failure. **Plusco 740 AW Hydraulic Oil** contains rust and oxidation inhibitors to protect against fluid break-down in normal heavy duty operations. **Plusco 740 AW Hydraulic Oil** is inhibited against formation of sludge and gum deposits commonly found when fluids are run at elevated temperatures for extended periods of time. **Plusco 740 AW Hydraulic Oil** exceeds most equipment operation requirements for medium to heavy duty service.

Plusco 740 AW Hydraulic Oil is available in 32, 46, and 68 grade.

TYPICAL SPECIFICATIONS

Color	Golden Yellow
Grade (ISO)	46
Viscosity: SUS @ 100°F	245
SUS @ 210°F	48
CST @ 40°C	6.60
CST @ 100°C	52.6
Pour Point F°	0
Flash Point °	405
Oxidation (D-943)	1800
Rust Test (D-655)	PASS

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.