



PLUSCO

Product Data Sheet

PLUSCO 741

Premium Anti-Wear Hydraulic Oil

PLUSCO 741 Premium Anti-Wear Hydraulic Oil is formulated to provide the ultimate in protection against wear in high output hydraulic systems. **PLUSCO 741** is manufactured using the highest quality base oil and a balanced combination of high tech additives to insure maximum protection to the hydraulic equipment. **PLUSCO 741** resist oxidation, decomposition and sludge formation at elevated temperatures. **PLUSCO 741** contains anti-foam additives, which provides rapid air separation for smooth hydraulic operation. This premium hydraulic oil is made with high viscosity index base oils that resist change in viscosity with temperature change. **PLUSCO 741** also contains an anti-rust additive to protect vital pump and cylinder components from rust and corrosion. This premium anti-wear hydraulic oil provides excellent performance on high-speed tubing and casing tongs.

TYPICAL SPECIFICATIONS

Color	Blue/Green tint
Classification	EP Lubricant
Grade	68
API Gravity	28.6
Flash Point	445°F
Viscosity	
SUS @ 100°F	320
SUS @ 210°F	53
Denison Test HG-2	Pass
Sperry-Vickers 35 VQ Series	Pass
ANSI / ASTM D-665 (Rust)	Pass
ASTM D-943 (Oxidation)	1500 + Hrs.
Additives	Anti-Wear Anti-Rust Anti-Foam Anti-Oxidant

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.