



# PLUSCO

## Product Data Sheet

### **PLUSCO 867**

### **H/T COMPLEX GRAPHITE H2S GREASE** **MULTI-PURPOSE SHEAR RESISTANT**

**PLUSCO#867** is a premium quality lubricant recommended for high temperature application primarily in bearing service. This multi-purpose lubricant is suitable for a variety of applications where mechanical shear resistance is required.

**PLUSCO#867** exhibits excellent antiwear properties and will retain its consistency under high temperature conditions. This lubricant is resistant to water washout and also provides protection against formation of rust and corrosion on bearings and other stress surfaces.

**PLUSCO#867** will service to temperatures over 500°F.

### **TYPICAL SPECIFICATIONS**

Type Lubricant	Lithium Complex/Graphite
Thickener	Lithium Polymer
Color	Black
Cone Pen ASTM D-217 (Worked)	310 - 340
NLGI Grade	No.1, No.2
Bearing Leakage D-1263	Pass
Dropping Point ASTM-D-566	500°F
Texture	Buttery
Water Resistance	Excellent
Other Characteristics	Fully Inhibited – EP. Anti-Wear, Anti-Oxidant, Anti-Rust and Corrosion Inhibited

PLUSCO, Inc., P.O. Box 7953, Houston, Texas 77270

Warranty: Because the conditions of use and the supervision of application are beyond the control of Plusco, Inc., we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent or representative or employee of this company is authorized to change this provision which relates to all goods delivered whether sold or delivered as samples or otherwise.